



NATROCHEM INC.
P.O. BOX 1205
SAVANNAH, GA 31402
(912) 236-4464 FAX: (912) 236-1919
www.natrochem.com

DATA SHEET NATRO-CEL[®] PE-A

Natro-Cel PE-A is a low molecular weight polyethylene grease, silicon dioxide blend, used as an internal lubricant and processing aid that helps mold flow, extruding and release. It also prevents tack in green rubber.

TEST	TEST METHOD	SPECIFICATIONS
Actives Content, %	QCL8.2.4-2-1	70 - 74
Carrier Content, %	QCL8.2.4-2-1	26 - 30

TYPICAL PROPERTIES

Actives Content, %		72
Carrier Content, %		28
Specific Gravity (Apparent)		1.06
Packaging	40# Net, Multi-wall Bags	
Color		Off-White

Date of Revision: 11/15/02

The information in this data sheet is derived from the best available sources and is believed to be accurate. However, no guarantee is expressed or implied regarding the accuracy of these data or the use of this product, nor are any statements in this bulletin intended as recommendations to use our products in the infringement of any patents.

OTHER NATROCHEM PRODUCTS

**DLC[®] - Galex[®] - Rosin Oils - Rosin Pitches - Tarene[™]
Natro-Flex[™] - Tar-Cel[®] - Natro-Cel[®]**